



优洛斯胶带

Adhesive Tapes

粘性胶带

玻璃纤维胶带

*Sicad Group*

---

The adhesive tape experience

司克集团



优洛斯胶带

# 分享粘性胶带的经验

the adhesive tape experience

## FG 10



### Filament tape 单面玻璃纤维胶带

Single sided tape, medium resistant, longitudinally reinforced, recommended to secure carton boxes or bundles. High adhesion and resistance to break. 单面玻璃纤维胶带，中等抗长率，适合包装，困扎用。据有高粘着力。

**Adhesive 胶水** : Synthetic rubber 合成橡胶

**Backing 基材** : Glass Fibre Reinforced + BOPP Film

### MAIN FEATURES



Adhesion 5



Tensile strength

### TECHNICAL DATA 技术资料

**Adhesion 粘着力** 25 N/25mm

**Color of the tape 颜色** 透明，白色

**Elongation to break 伸长率** 6 %

**Temperature resistance 耐温** 60 °C

**Tensile strength 抗张力** 575 N/25mm

**Total thickness 总厚度** 0.11 mm



优洛斯胶带

# 分享粘性胶带的经验

the adhesive tape experience

Industry /

# FG 13



### Filament tape 玻璃纤维胶带

Single sided tape, highly resistant, longitudinally reinforced, recommended to secure carton boxes or bundles. FG 10 version with stronger backing. Very high resistance to break. 单面玻璃纤维胶带，中等抗长率，适合包装，困扎用。比 FG10 更强，据有很高的抗张力。

**Adhesive 胶水** : Synthetic rubber 合成橡胶

**Backing 基材** : Glass Fibre Reinforced + BOPP Film

### MAIN FEATURES



Adhesion 5



Tensile strength

### TECHNICAL DATA 技术资料

**Adhesion 粘着力** 25 N/25mm

**Color of the tape 颜色** 透明，白色

**Elongation to break 伸长率** 7 %

**Temperature resistance 耐温** 60 °C

**Tensile strength 抗张力** 875 N/25mm

**Total thickness 总厚度** 0.14 mm



# 分享粘性胶带的经验

the adhesive tape experience

优洛斯胶带

Industry /

## FG BD



### Crossweave reinforced tape 网格玻璃纤维胶带

Single sided tape with high resistance to break, recommended to secure heavy packagings. High resistance to break also in transversal direction. 单面高抗张力玻纤胶带。推荐用于包装，困扎笨重的东西。

**Adhesive** 胶水: Synthetic rubber 合成橡胶

**Backing** 基材: Bidirectional Glass Yarn + BOPP Film

### MAIN FEATURES



Adhesion 5



Tensile strength

### TECHNICAL DATA 技术资料

**Adhesion** 粘着力 25 N/25mm

**Color of the tape** 颜色 透明, 白色

**Elongation to break** 伸长率 6 %

**Temperature resistance** 耐温 60 °C

**Tensile strength** 抗张力 650 N/25mm

**Total thickness** 总厚度 0.14 mm



优洛斯胶带

# 分享粘性胶带的经验

the adhesive tape experience

Industry /

# FP 14S



### Filament tape 高档玻璃纤维胶带

Single sided tape, longitudinal PET fibers reinforced PET backing. Highly resistant, recommended to fix and close aluminium coils. Clean removal from the last layer.  
单面玻纤胶带。高抗张力，建议固定和关闭铝线圈

**Adhesive 胶水:** Natural rubber 天然橡胶

**Backing 基材:** PET yarns + PET Film

### MAIN FEATURES



● ● ● ○ ○  
Tack 3



Tensile strength

### TECHNICAL DATA 技术资料

**Adhesion 粘着力** 7.5 N/25mm

**Color of the tape 颜色** Transparent 透明

**Elongation to break 伸长率** 14 %

**Temperature resistance 耐温** 60 °C

**Tensile strength 抗张力** 700 N/25mm

**Total thickness 总厚度** 0.195 mm