



优洛斯胶带

Adhesive Tapes

粘性胶带

家电产业与捆扎胶带

Sicad Group

The adhesive tape experience

司克集团



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

PP 500



Strapping tape 困扎胶带

Mono oriented pallet single sided tape, recommended to bundle pallets and for light reinforcement. Good resistance to break. 单面 MOPP 困扎胶带。适合用于困扎托盘与货物。据有高抗张力。

Adhesive 胶水 : Synthetic rubber 合成橡胶

Backing 基材 : MOPP

Applications 用途: 困扎

MAIN FEATURES



Adhesion 4



Tensile strength

TECHNICAL DATA 技术资料

Adhesion 粘着力 15 N/25mm

Color of the tape 颜色 Various 白色, 褐色, 黑色, 透明

Elongation to break 伸长率 35 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 425 N/25mm

Thickness of the backing 基材的厚度 50 µm

Total thickness 总厚度 0.072 mm



分享粘性胶带的经验

the adhesive tape experience

优洛斯胶带

Industry /

PP 800



High tensile strapping tape 高抗张力困扎胶带

Mono oriented pallet single sided tape, recommended to bundle pallets. High resistance to break. Maximum security. MOPP 困扎胶带，据有特别高的抗张力，适合困扎用

Adhesive 胶水 : Synthetic rubber 合成橡胶

Backing 基材 : MOPP

Applications 用途 : 困扎

MAIN FEATURES



Adhesion 4



Tensile strength

TECHNICAL DATA 技术资料

Adhesion 粘着力 15 N/25mm

Color of the tape 颜色 Various 白色, 黑色, 透明

Elongation to break 伸长率 35 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 650 N/25mm

Thickness of the backing 基材的厚度 75 µm

Total thickness 总厚度 0.097 mm



优洛斯胶带

分享粘性胶带的经验

the adhesive tape experience

PP 505



Holding tape MOPP 固定胶带

Medium resistant single sided tape, recommended to fix plastic parts inside refrigerators and freezers during manufacturing and transport. No chemical interaction with application surfaces. Removable without residues. Good resistance to break. 单面中抗张力，适合零时固定冰箱零件用，不留残胶。

Adhesive 胶水 : Natural rubber 天然橡胶

Backing 基材 : MOPP

Applications 用途: 零时固定家电产业零件

MAIN FEATURES



● ● ○ ○ ○
Adhesion 2



Tensile strength



Removable

TECHNICAL DATA 技术资料

Adhesion 粘着力 4.3 N/25mm

Elongation to break 伸长率 33 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 350 N/25mm

Thickness of the backing 基材的厚度 50 μm

Total thickness 总厚度 0.07 mm



分享粘性胶带的经验

the adhesive tape experience

优洛斯胶带

PP 550



Holding tape blue MOPP 固定胶带

Medium resistant single sided tape, recommended to fix plastic parts inside refrigerators and freezers during manufacturing and transport. No chemical interaction with application surfaces. Removable without residues. Good resistance to break. 单面中抗张力，适合零时固定冰箱零件用，不留残胶。

Adhesive 胶水: Natural rubber 天然橡胶

Backing 基材: MOPP

Applications 用途: 零时固定家电产业零件

MAIN FEATURES



● ● ○ ○ ○
Adhesion 2



Tensile strength



Removable

TECHNICAL DATA 技术资料

Adhesion 粘着力 4.3 N/25mm

Elongation to break 伸长率 33 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 350 N/25mm

Thickness of the backing 基材的厚度 55 μm

Total thickness 总厚度 0.076 mm



分享粘性胶带的经验

the adhesive tape experience

优洛斯胶带

PP 552



Holding tape blue MOPP 固定胶带

Medium resistant single sided tape, recommended to fix plastic parts inside refrigerators and freezers during manufacturing and transport. No chemical interaction with application surfaces. Removable without residues. Good resistance to break. 单面中抗张力，适合零时固定冰箱零件用，不留残胶。据有比 PP550 高的粘着力

Adhesive 胶水: Natural rubber 天然橡胶

Backing 基材: MOPP

Applications 用途: 零时固定家电产业零件

MAIN FEATURES



Adhesion 5



Tensile strength



Removable

TECHNICAL DATA 技术资料

Adhesion 粘着力 8 N/25mm

Elongation to break 伸长率 33 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 350 N/25mm

Thickness of the backing 基材的厚度 55 µm

Total thickness 总厚度 0.08 mm



优洛斯胶带

分享粘性胶带的经验

the adhesive tape experience

Industry /

PP 850



High tensile, holding tape 高抗张力 MOPP 固定胶带

Stronger version of the PP 505. Recommended to fix plastic parts inside refrigerators and freezers during manufacturing and transport. No chemical interaction with application surfaces. Removable without residues. PP850 据有比 PP505 高抗张力与粘着力。适合用于生产和运输中固定冰箱内部的塑料零件，和塑料的表面不起化学作用，拔离后不留残胶。

Adhesive 胶水: Natural rubber 天然橡胶

Backing 基材: MOPP

Applications 用途: 零时固定家电产业零件

MAIN FEATURES



Adhesion 3



Tensile strength



Removable

TECHNICAL DATA 技术资料

Adhesion 粘着力 5 N/25mm

Elongation to break 伸长率 40 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 615 N/25mm

Thickness of the backing 基材的厚度 90 µm

Total thickness 总厚度 0.113 mm



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

Industry /

PP 8502 HT



High tensile, holding tape 高抗张力 MOPP 固定胶带

Stronger version of the PP 505. Recommended to fix plastic parts inside refrigerators and freezers during manufacturing and transport. No chemical interaction with application surfaces. Removable without residues. PP8502 HT 据有比 PP850 高的粘着力。适合用于生产和运输中固定冰箱内部的塑料零件，和塑料的表面不起化学作用，拔离后不留残胶。

Adhesive 胶水: Natural rubber 天然橡胶

Backing 基材: MOPP

Applications 用途: 零时固定家电产业零件

MAIN FEATURES



Adhesion 5



Tensile strength



Removable

TECHNICAL DATA 技术资料

Adhesion 粘着力 9 N/25mm

Elongation to break 伸长率 40 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 615 N/25mm

Thickness of the backing 基材的厚度 90 µm

Total thickness 总厚度 0.113 mm



分享粘性胶带的经验

the adhesive tape experience

优洛斯胶带

Industry /

PP 855



High tensile, holding tape 高抗张力 MOPP 固定胶带

Stronger version of the PP 550. Recommended to fix plastic parts inside refrigerators and freezers during manufacturing and transport. No chemical interaction with application surfaces. Removable without residues. PP855 据有比 PP550 高抗张力与粘着力。适合用于生产和运输中固定冰箱内部的塑料零件，和塑料的表面不起化学作用， 拔离后不留残胶。

Adhesive 胶水: Natural rubber 天然橡胶

Backing 基材: MOPP

Applications 用途: 零时固定家电产业零件

MAIN FEATURES



Adhesion 3



Tensile strength



Removable

TECHNICAL DATA 技术资料

Adhesion 粘着力 5 N/25mm

Elongation to break 伸长率 40 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 615 N/25mm

Thickness of the backing 基材的厚度 90 µm

Total thickness 总厚度 0.113 mm



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

Industry /

PP 8552 HT



High tensile, holding tape 高抗张力 MOPP 固定胶带

Stronger version of the PP 550. Recommended to fix plastic parts inside refrigerators and freezers during manufacturing and transport. No chemical interaction with application surfaces. Removable without residues. PP8552 HT 据有比 PP855 高的粘着力。适合用于生产和运输中固定冰箱内部的塑料零件，和塑料的表面不起化学作用，拔离后不留残胶。

Adhesive 胶水: Natural rubber 天然橡胶

Backing 基材: MOPP

Applications 用途: 零时固定家电产业零件

MAIN FEATURES



Adhesion 5



Tensile strength



Removable

TECHNICAL DATA 技术资料

Adhesion 粘着力 9 N/25mm

Elongation to break 伸长率 40 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 615 N/25mm

Thickness of the backing 基材的厚度 90 µm

Total thickness 总厚度 0.113 mm